

DATASHEET

Extension Cable C14 180° - C13 180°, Dual Lock, Black, 1.5 m



General data

With „Dual-Lock“: prevents accidentally removing of the C13 jack from devices

After connecting, the C13 jack only can be released after sliding back the red latch
10 A / 250 V VDE tested (optional: orange, blue, grey, white)

Technical properties

Colour outer sheath	black
Connection 1	Cold device plug (IEC 60320)
Connection 2	Cold device plug straight, female
Halogen free	No
Jacket material	Polyvinylchlorid (PVC)
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Protective conductor	True
Spiralized cable	False

This datasheet was created automatically on 29-01-2026 . Technical changes reserved.



DATASHEET

Extension Cable C14 180° - C13 180°, Dual Lock, Black, 1.5 m

Temperature resistance	5 70 °C
With cord switch	False

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Degree of protection	Length	Nominal current	Nominal voltage	With protective conductor	Nominal cross section conductor	Outer diameter approx.
EK620SW.0,5	Extension Cable C14 180° - C13 180°, Dual Lock, Black, 0.5 m	black	IP20 according to EN60529	0.5 m	10 A	250 V	Ja	1.04 mm²	8.0
EK620SW.1	Extension Cable C14 180° - C13 180°, Dual Lock, Black, 1 m	black	IP20 according to EN60529	1.0 m	10 A	250 V	Ja	1.04 mm²	8.0
EK620SW.1,5	Extension Cable C14 180° - C13 180°, Dual Lock, Black, 1.5 m	black	IP20 according to EN60529	1.5 m	10 A	250 V	Ja	1.04 mm²	8.0
EK620SW.2	Extension Cable C14 180° - C13 180°, Dual Lock, Black, 2 m	black	IP20 according to EN60529	2.0 m	10 A	250 V	Ja	1.04 mm²	8.0
EK620SW.3	Extension Cable C14 180° - C13 180°, Dual Lock, Black, 3 m	black	IP20 according to EN60529	3.0 m	10 A	250 V	Ja	1.04 mm²	8.0

This datasheet was created automatically on 29-01-2026 . Technical changes reserved.

