

DATASHEET

Warm Device Extension C14 180° - C15 180°, Black, 1 m,
3 x 1.00 mm²



General data

Plug IEC60320/C14 to jack IEC60320/C15
10 A / 250 V VDE tested
Cable H50RN-F 3G(rubber cable)
Colour black

Technical properties

Colour outer sheath	black
Connection 1	Cold device plug (IEC 60320)
Connection 2	Hot device plug, female
Halogen free	No
Jacket material	rubber
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Protective conductor	True
Spiralized cable	False
Temperature resistance	-35 70 °C
With cord switch	False

Available variants

This datasheet was created automatically on 29-01-2026 . Technical changes reserved.



DATASHEET

Warm Device Extension C14 180° - C15 180°, Black, 1 m, 3 x 1.00 mm²

ArtNr.	Bezeichnung	Colour outer sheath	Degree of protection	Length	Nominal current	Nominal voltage	With protective conductor	Nominal cross section conductor	Outer diameter approx.
EK585.1V2	Warm Device Extension C14 180° - C15 180°, Black, 1 m, 3 x 1.00 mm ²	black	IP20 according to EN60529	1.0 m	10 A	250 V	Ja	1.0 mm ²	7.3 mm
EK585.2V2	Warm Device Extension C14 180° - C15 180°, Black, 2 m, 3 x 1.00 mm ²	black	IP20 according to EN60529	2.0 m	10 A	250 V	Ja	1.0 mm ²	7.3 mm
EK585.3V2	Warm Device Extension C14 180° - C15 180°, Black, 3 m, 3 x 1.00 mm ²	black	IP20 according to EN60529	3.0 m	10 A	250 V	Ja	1.0 mm ²	7.3 mm

This datasheet was created automatically on 29-01-2026 . Technical changes reserved.

