

DATASHEET

19" Wall Housing 16U, Depth 800 mm, Pre-Assembled, RAL9005



General data

Steel sheet housing with screwed frame, pre-assembled, self-ventilated, detachable

Prepared for plug & play fan unit Art.-No. 691656GR

Also suitable for mounting of 2 single fans in roof

Side walls detachable, lockable, lock equal to front door

Roof, bottom and rear wall with pre-punched openings for cable entry (145 x 70 mm)

Inside front and rear sided each 2 x 19" profile rails, galvanised, depth adjustable

Max. distance of 19" levels (front/rear) 625 mm

Front door with latch locking and window of certified safety glass (thickness 4 mm)

Cabinet parts inside fully earthed

Paint finish RAL9005, jet black

Protection degree IP20

Included accessories: 1 x brush strip, 1 x plastic cover for cable entry, 1 x set of cage nuts (PU 20 pcs.), 2 x key

Delivery in transport packaging, from 30 kg / 12U on disposable pallet

Technical properties

Cabinet Series	19" Wall Housing Depth 800 mm, pre-assembled
Degree of protection	IP20
Demountable	True

This datasheet was created automatically on 17-12-2025 . Technical changes reserved.



DATASHEET

19" Wall Housing 16U, Depth 800 mm, Pre-Assembled, RAL9005

Material	Steel
Model	With permanent frame
Modular spacing	482.6 mm (19 inch)
Mounting level	Front and rear
Number of cartons	1
Number of doors	1
Surface finishing	Powder coating
Type of front door	Glass door 1-part
Type of profile rail	Crank
Type of ventilation	Passive
With earthing	True
With front door	True
With roof plate	True
With sidewall	True

Available variants

ArtNr.	Bezeichnung	Color	Depth	Height	Max. Load	Max. load capacity	Number of height units	Width	RAL-number
691912TS.80	19" Wall Housing 12U, Depth 800 mm, Pre-Assembled, RAL9005	black	800 mm	634 mm	80 kg	80 kg	12 U	600 mm	7035
691916TS.80	19" Wall Housing 16U, Depth 800 mm, Pre-Assembled, RAL9005	black	800 mm	812 mm	80 kg	80 kg	16 U	600 mm	7035
691920TS.80	19" Wall Housing 20U, Depth 800 mm, Pre-Assembled, RAL9005	black	800 mm	990 mm	80 kg	80 kg	20 U	600 mm	7035
691922TS.80	19" Wall Housing 22U, Depth 800 mm, Pre-Assembled, RAL9005	black	800 mm	1078 mm	80 kg	80 kg	22 U	600 mm	7035
691926TS.80	19" Wall Housing 26U, Depth 800 mm, Pre-Assembled, RAL9005	black	800 mm	1256 mm	80 kg	80 kg	26 U	600 mm	7035

This datasheet was created automatically on 17-12-2025 . Technical changes reserved.

