



DATASHEET

19" Server Cabinet PRO 42U, 800x1000 mm, F+R 2-Part, RAL7035



General data

19" server cabinet according to DIN41494

Steel sheet housing with screwed frame, completely pre-assembled, self-ventilated, dismantlable

Inside front and rear 4 x 19" profiles (2 front, 2 rear-sided), galvanised, step-less depth-adjustable

Contrariwise numbering of rack units at the 19" profiles

Front and rear door with 3-point turning handle (up to 24U 1-point), lockable, incl. profile half-cylinder acc. to DIN18252 / EN 1303

Profile half-cylinder exchangeable by customer (30/10 mm)

Door stop for front and rear door possible left- or right-sided

Detachable side walls with 2 x latch locking (lock equal to the door lock)

Cabinets stackable side-by-side with and without removal of the side walls, baying set (Art.-No. PRO-ANR0X), otherwise screwable via screw set M6

Roof and bottom with 4/6 pre-punched openings for cable entry (450 x 90 mm), for 600 mm cabinet width cable entry only rear

Roof prepared for accommodation of 2-fan or 4-fan units, bottom with pre-punched opening for filter or cable entry modules

Internal earthing of all cabinet sections

Pre-assembled earthing bar rear-sided in the middle of the cabinet (ports: 20 x M5 + 2 x 8 mm)

Max. load 1000 kg (depths 600 / 800 mm) resp. 1360 kg (depths 1000 / 1200 mm for >24U)

This datasheet was created automatically on 30-01-2026 . Technical changes reserved.



DATASHEET

19" Server Cabinet PRO 42U, 800x1000 mm, F+R 2-Part, RAL7035

Paint finish RAL7035, light grey / RAL9005, jet black

Protection degree IP20

Included accessories: 1 x brush, 1 x set of captive nuts (PU 20 pcs.), earthing bar and earthing cables, 4 x levelling feet M12, 2 x key

Delivery in transport packaging on disposable pallet

Technical properties

Active air conditioning	False
Air inlet floor	Breakout opening type A (380 x 380 mm), e.g. for filter or cable entry modules
Cabinet Series	PRO
Cable entry roof/floor	Roof and base each with 4 pre-cut, breakable openings, all around, each 450 x 89 mm (re-sealable with a 19" 2U blanking plate)
Category	19" server cabinet according to DIN41494
Degree of protection	IP20 according to EN60529
Demountable	True
Door hinge reversible front door	True
Door hinge reversible rear door	True
Door opening angle front door	270 °
Door opening angle rear door	270 °
Frame	screwed together, completely pre-assembled
Material	Steel
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front and rear
PHC replaceable front door	True, according to DIN18252 (30/10 mm)
PHC replaceable rear door	True
Packaging	Delivery in transport packaging on a disposable pallet
Perforation level front door	> 80 %
Perforation level rear door	> 80 %
Scope of delivery	1x cabinet, 1 x brush strip, 1 x cage nut set (20 pieces per pack), grounding rail and grounding cable, 4 x M12 leveling feet, 2 x keys
Stackable	True
Surface finishing	Powder coating
Type of back door	Steel perforated 2-part
Type of front door	Steel perforated 2-part
Type of profile rail	Crank

This datasheet was created automatically on 30-01-2026 . Technical changes reserved.



DATASHEET

19" Server Cabinet PRO 42U, 800x1000 mm, F+R 2-Part, RAL7035

Type of ventilation	Passive
With backside door	True
With earthing	True
With front door	True
With roof plate	True
With sidewall	True
With socket	False

Available variants

ArtNr.	Bezeichnung	Color	Depth	Front door locking system	Material front door	Material rear door	Max. load capacity	Number of height units	Rear door locking system	Width	With glazed door	With cable management	With vertical	Height	RAL-number	Number of doors
PRO-3380TS.P2	19" Server Cabinet PRO 33U, 800x1000 mm, F+R 2-Part, RAL9005	black	1000 mm	3-point rod locking mechanism with swivel lever	Steel	Steel	1360 kg	33 HE	3-point rod locking mechanism with swivel lever	797 mm	False	False		1563 mm	9005	2
PRO-4280TS.P2	19" Server Cabinet PRO 42U, 800x1000 mm, F+R 2-Part, RAL9005	black	1000 mm	3-point rod locking mechanism with swivel lever	Steel	Steel	1360 kg	42 HE	3-point rod locking mechanism with swivel lever	797 mm	False	False		1963 mm	9005	2
PRO-4780TS.P2	19" Server Cabinet PRO 47U, 800x1000 mm, F+R 2-Part, RAL9005	black	1000 mm	3-point rod locking mechanism with swivel lever	Steel	Steel	1360 kg	47 HE	3-point rod locking mechanism with swivel lever	797 mm	False	False		2186 mm	9005	2
PRO-4280GR.P2	19" Server Cabinet PRO 42U, 800x1000 mm, F+R 2-Part, RAL7035	grey	1000 mm	3-point rod locking mechanism with swivel lever	Steel	Steel	1360 kg	42 HE	3-point rod locking mechanism with swivel lever	797 mm	False	False		1963 mm	7035	2

This datasheet was created automatically on 30-01-2026 . Technical changes reserved.

