


Data sheet



Description

The Uniboot OS2 fibre optic patch cable LC-DX-LC-DX is designed for high-performance fibre connections in professional network infrastructures. It features an integrated, simple polarity reversal, allowing flexible adjustment during installation. The pull-boot design relieves strain on connectors and housings via a pulling mechanism and reduces the risk of cable damage. The halogen-free LSZH jacket is flame-retardant, low-smoke and contributes to increased safety in indoor environments. - OS2 single-mode fibre for long-distance applications - Integrated polarity reversal in uniboot design - Halogen-free and low-smoke Standards & approvals - IEC 60793-2-50 - IEC 60754-2 - IEC 61034 - UL94 V-0

Connections

Connection 1	LC-DX
Alignment 1	180°
Type of cut 1	UPC
Housing 1	Plastic
Housing color 1	Blue
Connection 2	LC-DX
Alignment 2	180°
Cut type 2	UPC
Housing 2	Plastic
Housing color 2	Blue



Cable


Typ	Figure 0
Fiber	Singlemode OS2
Fiber type	9/125 μ
Fiber count	2
Outer sheath material	LSZH
Outer diameter	2,0 mm

Signal transmission

Standard	IEC 60793-2-50
----------	----------------

Standards

Approval	-
Compliance	RoHS Reach CE
Halogen-free	IEC60754-2, IEC 61034
UL listed	UL94V-0
Fire behavior	IEC60332-1
Temperature range	-20°C ~ +80°C



Item No.	Colour	Length	Tolerance	EAN
61955D-PB-0,5M	Yellow	0.5 m	+50/-0 mm	4262565910354
61955D-PB-1,0M	Yellow	1.0 m	+100/-0 mm	4262565910361
61955D-PB-2,0M	Yellow	2.0 m	+100/-0 mm	4262565910378
61955D-PB-3,0M	Yellow	3.0 m	+100/-0 mm	4262565910385
61955D-PB-5,0M	Yellow	5.0 m	+100/-0 mm	4262565910392
61955D-PB-7,5M	Yellow	7.5 m	+100/-0 mm	4262565910408
61955D-PB-10,0M	Yellow	10.0 m	+1000/-0 mm	4262565910415
61955D-PB-15,0M	Yellow	15.0 m	+1500/-0 mm	4262565910422
61955D-PB-20,0M	Yellow	20.0 m	+2000/-0 mm	4262565910439
61955D-PB-25,0M	Yellow	25.0 m	+2500/-0 mm	4262565910446
61955D-PB-30,0M	Yellow	30.0 m	+3000/-0 mm	4262565910453

