

DATASHEET

65W 2x USB-C + USB-A Charger PD3.0 GaN QC3.0 Input: 100-240V~1.5A 50/60Hz, white



General data

65W 2x USB-C + USB-A Charger - High-Performance GaN Adapter for Professional Use

The 65W GaN charger offers maximum power in a compact form. Equipped with two USB-C Power Delivery ports and one USB-A port, it can charge up to three devices simultaneously. GaN (Gallium Nitride) technology ensures efficiency, minimal heat, and reliability - ideal for smartphones, tablets, and laptops. Perfect for office desks, retail environments, and mobile professionals.

Specifications:

- Output Power: 65W Fast Charging (Power Delivery)
- Technology: GaN (Gallium Nitride)
- Ports: 2x USB-C + 1x USB-A
- Without charging cable (white)
- Universal compatibility with mobile devices and laptops

Applications:

Suitable for office use, wholesale, conferences, and travel.

Technical properties

Cable connection on the device

All USB-C-PD-device

This datasheet was created automatically on 23-03-2026 . Technical changes reserved.



DATASHEET

65W 2x USB-C + USB-A Charger PD3.0 GaN QC3.0 Input: 100-240V~1.5A 50/60Hz, white

Cable included (Yes/No)	False
Certifications	CE&RoHS
Charging current	Output :C1/C2: 5V/9V 3A,12V/15V 3A,20V 3.25A A1 Output: 5V/3A,9V/2A,12V/1.5A C1+C2: 45W+20W=65W C1+A1:45W+18W=63W C2+A1: 5V/3A=15W C1+(C2+A1):45W+15W=60W
Colour	white
GaN technology (Yes/No)	True
Material	ABS+PC
Maximum load capacity	65 W
Operating temperature	0 - 40 °C
Overvoltage protection	True
Safety systems / protection functions	CE&RoHS / ocp, ovp, scp
Scope of delivery	Charger
Storage temperature	-20 - +80 °C
Suitable for (country)	All countries
USB ports (number & type)	2xUSB-C & 1xUSB-A
Warranty	24 Months

Available variants

ArtNr.	Bezeichnung	Frequency supply voltage	Height	High-speed battery charger	Length	Nominal voltage	Width
G651A2CE	65W 2x USB-C + USB-A Charger PD3.0 GaN QC3.0 Input: 100-240V~1.5A 50/60Hz, white	50 - 60 Hz	31 mm	PD3.0 QC3.0	86 mm	100 - 240 V	48 mm

This datasheet was created automatically on 23-03-2026 . Technical changes reserved.

