

DATASHEET

100W 2x USB-C + USB-A Charger PD3.0 GaN QC3.0 Input: 100-240V~1.5A 50/60Hz, white



General data

100W 2x USB-C + USB-A Charger - High-Performance GaN Power Adapter for Professional Use

The 100W GaN charger delivers outstanding power and efficiency for demanding environments. With two USB-C Power Delivery ports and one USB-A output, it can charge multiple devices simultaneously - from laptops to smartphones. GaN (Gallium Nitride) technology ensures reduced heat, smaller size, and top efficiency.

Specifications:

- Output Power: 100W Fast Charging (Power Delivery)
- Technology: GaN (Gallium Nitride)
- Ports: 2x USB-C + 1x USB-A
- Without charging cable (white)
- Compact, high-efficiency design

Applications:

Ideal for offices, retail, wholesale, and professional users.

Technical properties

Cable connection on the device	All USB-C-PD-device
Cable included (Yes/No)	False

This datasheet was created automatically on 23-03-2026 . Technical changes reserved.



DATASHEET

**100W 2x USB-C +USB-A Charger PD3.0 GaN QC3.0 Input:
100-240V~1.5A 50/60Hz, white**

Certifications	CE&RoHS
Charging current	A (27W Max) Dual-port common use:C1 +C2(65W/30w Max+ 30W /65W Max)C1 +A(65W Max+27Max)C2 +A(5V4.8A,24W Max)2C+A common use:C1 65WMax+5V4.8A 24W
Colour	white
GaN technology (Yes/No)	True
Material	ABS+PC
Maximum load capacity	100 W
Operating temperature	0 - 40 °C
Overvoltage protection	True
Safety systems / protection functions	CE&RoHS / ocp, ovp, scp
Scope of delivery	Charger
Storage temperature	-20 - +80 °C
Suitable for (country)	All countries
USB ports (number & type)	2xUSB-C & 1xUSB-A
Warranty	24 Months

Available variants

ArtNr.	Bezeichnung	Frequency supply voltage	High-speed battery charger	Nominal voltage
G1001A2CE	100W 2x USB-C +USB-A Charger PD3.0 GaN QC3.0 Input: 100-240V~1.5A 50/60Hz, white	50 - 60 Hz	PD3.0 QC3.0	100 - 240 V

This datasheet was created automatically on 23-03-2026 . Technical changes reserved.

