

# DATASHEET

## Power Cable CEE7/7 90° - Open End WES, 3.0 m, 3 x 1.00 mm<sup>2</sup>



### General data

16 A / 250 V VDE tested  
 Open End assembled with wire end sleeves  
 Wire end sleeves for 1.8 m: L = 6 mm, Ø 1.7 mm, yellow insulator  
 Wire end sleeves for 3 + 5 m: L = 8 mm, Ø 1.7 mm, red insulator  
 Cable colour black  
 Suitable for Germany, Belgium, France and further

### Technical properties

Colour outer sheath	black
Connection 1	Plug with protective contact (type F), right-angled
Connection 2	Cable end sleeve
Halogen free	No
Jacket material	Polyvinylchlorid (PVC)
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Protective conductor	True
Spiralized cable	False
With cord switch	False

### Available variants

This datasheet was created automatically on 15-05-2026 . Technical changes reserved.



# DATASHEET

## Power Cable CEE7/7 90° - Open End WES, 3.0 m, 3 x 1.00 mm<sup>2</sup>

ArtNr.	Bezeichnung	Colour outer sheath	Length	Nominal current	Nominal voltage	Reaction-to-fire class according to EN 13501-6	With protective conductor	Nominal cross section conductor	Outer diameter approx.
EK504AE.1,8	Power Cable CEE7/7 90° - Open End WES, 1.8 m, 3 x 0.75 mm <sup>2</sup>	black	1.8 m	16 A	250 V	Dca	Ja	0.75 mm <sup>2</sup>	6.8 mm
EK504AE.3	Power Cable CEE7/7 90° - Open End WES, 3.0 m, 3 x 1.00 mm <sup>2</sup>	black	3.0 m	16 A	250 V	Dca	Ja	1.0 mm <sup>2</sup>	7.1 mm
EK504AE.5	Power Cable CEE7/7 90° - Open End WES, 5.0 m, 3 x 1.00 mm <sup>2</sup>	black	5.0 m	16 A	250 V	Dca	Ja	1.0 mm <sup>2</sup>	7.1 mm

This datasheet was created automatically on 15-05-2026 . Technical changes reserved.

