

Data sheet



Features

- Steel-armored & robust: Impact-resistant and extremely resilient.
- Event-ready: Specially developed for the requirements of the event industry.
- Dust-protected: Includes protective caps for maximum service life.
- Quickly identifiable: Black label with all important information.



Description

The steel-armored fiber optic duplex patch cable with LC connectors from the Black Series was specially developed for demanding applications in event and stage technology. The robust figure-8 cable construction provides high resistance to foot traffic and mechanical stability in mobile installations. High-quality black connectors and captive dust protection caps reliably protect the interfaces. - Robust figure-8 cable construction for high mechanical stability - Captive dust protection caps for connector protection - Cable labels indicating length, fiber type, and connectors

Connections

Connection 1	LC-DX
Alignment 1	180°
Quantity 1	1
Type of cut 1	UPC
Housing 1	Plastic
Housing color 1	black
Connection 2	LC-DX
Alignment 2	180°
Quantity 2	1
Cut type 2	UPC
Housing 2	Plastic
Housing color 2	black



Cable

Typ	Figure 8
Cable structure	-
Fiber	Multimode OM4
Fiber type	50/125 μ
Fiber count	2
Outer sheath material	LSOH
Outer diameter	3.0mm

Standards

Approval	-
Compliance	RoHS Reach CE
Halogen-free	Halogen-free according to EN 50267-2-3
Temperature range	-20°C ~ +70°C

Item No.	Colour	Length	Tolerance	EAN
610555D-0,5M4	black	0.5 m	+50/-0 mm	4260424511292
610555D-1,0M4	black	1.0 m	+50/-0 mm	4260424511308
610555D-2,0M4	black	2.0 m	+100/-0 mm	4260424511315
610555D-3,0M4	black	3.0 m	+100/-0 mm	4260424511322
610555D-5,0M4	black	5.0 m	+100/-0 mm	4260424511339
610555D-7,5M4	black	7.5 m	+100/-0 mm	4260424511346
610555D-10,0M4	black	10.0 m	+100/-0 mm	4260424511353
610555D-15,0M4	black	15.0 m	+150/-0 mm	4260424511360
610555D-20,0M4	black	20.0 m	+200/-0 mm	4260424511377
610555D-25,0M4	black	25.0 m	+250/-0 mm	4260424511384
610555D-30,0M4	black	30.0 m	+300/-0 mm	4260424511391

