DATASHEET

RJ45 Connector STP, Cat.6A, field-terminable, bayonet













General data

Assemble professional network connections quickly and securely

EFB's field-terminable Cat.6A RJ45 connector enables simple and reliable termination of shielded Cat.6A, Cat.7, and Cat.7A installation cables directly on-site. Thanks to the integrated cable pre-sorter with printed TIA/EIA 568 A/B color codes, wiring is quick and error-free. The robust bayonet screw connection ensures secure cable fastening and reliable strain relief. The included dust cap protects the contacts from dirt and damage during storage and operation.

Your benefits at a glance

Cat.6A performance – supports data transfers up to 10 Gigabit Ethernet
Quick and easy installation – Color-coded cable pre-sorter simplifies installation

This datasheet was created automatically on 31-07-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

RJ45 Connector STP, Cat.6A, field-terminable, bayonet

Secure strain relief – Stable cable fastening via bayonet screw connection

Product highlights

Field-terminable RJ45 connector for shielded Cat.6A, Cat.7, and Cat.7A installation cables
Suitable for conductor cross-sections from **AWG22/1 to AWG24/1**
Cable pre-sorter for easy and clean installation
Pair management according to **TIA/EIA 568 A/ B**
Color codes printed directly on the cable pre-sorter
Supports **PoE up to 4PPoE according to IEEE 802.3bt**
Rugged bayonet screw connection for secure cable attachment and strain relief
Includes a dust cap to protect the contacts

Package Contents

1 × Cat.6A RJ45 connector

Technical properties	
360° shield contact	True
AWG-range	24 – 22
Cable diameter	8,5
Category	6A (IEC)
Complaint to UL94	V-0
Connection type	Insulation displacement connector
Contact Resistance	≤ 20
Current capacity	1,5
Dielectric Withstanding Voltage	1000
Dust cover	true
Insertion force	≤ 30
Insulation Resistance	≥ 500
Mating cycles	≥750
Model	plug
Operating Temperature	-10 – 60
Screened	True
Suitable for round cable	False
Suitable for solid core	True
Type of connector	RJ45 8(8)

This datasheet was created automatically on 31-07-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

RJ45 Connector STP, Cat.6A, field-terminable, bayonet

Type of locking	Screw lock

Available variants

ArtNr.	Bezeichnung	Color
89061.1	RJ45 Connector STP, Cat.6A, field-terminable, bayonet	silver

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION