


DATASHEET

65W Wireless Charging Station 3x USB-C™ / 2x USB-A 1.5m black



General data

Charger that allows you to charge your phone or other compatible devices simply by placing them in the center of the charging base or using the USB-A/USB-C™ ports
 2 x 18W USB-A ports and 3 x 65W USB-C™ ports; supports wireless charging up to 15W (5W, 7.5W, 10W, 15W)
 Overvoltage and short circuit protection
 1.5m cable with 2-pin European plug included

Environmental characteristics

Use within 2000 m altitude
 Operating temperature: -20°C to 25°C
 Humidity: 20% to 80% RH

This datasheet was created automatically on 14-09-2026 . Technical changes reserved.



DATASHEET

65W Wireless Charging Station 3x USB-C™/2x USB-A 1.5m black

Technical properties	
Cable included (Yes/No)	True
Cable length	1.5 Meter
Colour	black
GaN technology (Yes/No)	True
Material	Plastic+PC+ABS
Maximum load capacity	65 W
Operating temperature	-20 - 25 °C
Overvoltage protection	True
USB ports (number & type)	2x USB-A, 3x USB-C

Available variants				
ArtNr.	Bezeichnung	Height	Length	Width
I-CHARGE-WR65AC	65W Wireless Charging Station 3x USB-C™/2x USB-A 1.5m black	36 mm	88 mm	98 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 14-09-2026 . Technical changes reserved.

