

DATASHEET

FTTx compact junction box, connection: 2x SC-Simplex/L-C-Duplex



General data

FTTX compact junction box with dimensions 100 x 80 x 23 mm

An adjustable fiber overlength cassette is mounted in the box for an easier work on cable inlets or connecting an adapter. The splice protection holder is also in the fiber overlength cassette. There are breakouts for 2 cable inlets in the box and also 2 breakouts for flangeless SC-Simplex or LC-Duplex adapters.

Technical properties

Cable entry without cable gland	2
Cable sheath support	False
Colour	white
Dimensions	100x80x22 mm
Foreign body and contact protection	Protection against medium-sized foreign bodies
Hinged splice cassette	True
Holder for gas blocker	False
Holder for splitter	False
IP Protection	IP20
Material	Plastic
Max. Assembly (Adapter)	2

This datasheet was created automatically on 14-10-2026 . Technical changes reserved.

DATASHEET

FTTx compact junction box, connection: 2x SC-Simplex/L-C-Duplex

Mounting method	Wall mounting
Number of Fibres	4
Operating Temperature	-20 - 60 °C
Possibility of mast mounting	False
Scope of application	Indoor
Suitable for adapter	SC Simplex/LC Duplex/E2000®
Type of Splice protection	Thermo
Water protection	Without protection
With Fiber overlength cassette	True
With plug protection	False

Available variants

ArtNr.	Bezeichnung	Access Control
53700.2	FTTx compact junction box, connection: 2x SC-Simplex/LC-Duplex	Without

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 14-10-2026 . Technical changes reserved.

