

DATASHEET

19" Server Cabinet PRO 42U, 800x1000 mm, F=1-P R=2-P,
RAL9005



General data

19" server cabinet according to DIN41494

Steel sheet housing with screwed frame, completely pre-assembled, self-ventilated, dismountable

Inside front and rear 4 x 19" profiles (2 front, 2 rear-sided), galvanised, step-less depth-adjustable

Contrariwise numbering of rack units at the 19" profiles

Front and rear door with 3-point turning handle (up to 24U 1-point), lockable, incl. profile half-cylinder acc. to DIN18252 / EN 1303

Profile half-cylinder exchangeable by customer (30/10 mm)

Door stop for front and rear door possible left- or right-sided

Detachable side walls with 2 x latch locking (lock equal to the door lock)

Cabinets stackable side-by-side with and without removal of the side walls, baying set (Art.-No. PRO-ANR0X), otherwise screwable via screw set M6

Roof and bottom with 4/6 pre-punched openings for cable entry (450 x 90 mm), for 600 mm cabinet width cable entry only rear

Roof prepared for accommodation of 2-fan or 4-fan units, bottom with pre-punched opening for filter or cable entry modules

Internal earthing of all cabinet sections

Pre-assembled earthing bar rear-sided in the middle of the cabinet (ports: 20 x M5 + 2 x 8 mm)

Max. load 1000 kg (depths 600 / 800 mm) resp. 1360 kg (depths 1000 / 1200 mm for >24U)

This datasheet was created automatically on 02-01-2023 . Technical changes reserved.

DATASHEET

19" Server Cabinet PRO 42U, 800x1000 mm, F=1-P R=2-P, RAL9005

Paint finish RAL7035, light grey

Protection degree IP20

Included accessories: 1 x brush, 1 x set of captive nuts (PU 20 pcs.), earthing bar and earthing cables, 4 x levelling feet M12, 2 x key

Delivery in transport packaging on disposable pallet

Allgemeine Daten

With front door	True
Type of ventilation	Passive
With backside door	True
Demountable	True
Surface finishing	With powder coating
With roof plate	True
Type of front door	Steel perforated 1-part
Modular spacing	482,6 mm (19 inch)
With sidewall	True
Mounting level	Front and rear
With socket	False
Model	With permanent frame
With earthing	True
Material	steel
Degree of protection (IP)	IP20
Type of back door	Steel perforated 2-part
Type of profile rail	Crank

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Front door locking system	Material front door	Material rear door	Max. Load Capacity	Number of height units	Rear door locking system	Width	With glazed door	With vertical cable management	Höhe	RAL-Nummer	Anzahl der Türen
PRO-2780TS.P1P2	19" Server Cabinet PRO 27U, 800x1000 mm, F=1-P R=2-P, RAL9005	black	1000 mm	-	Steel	Steel	1360 kg	27 U	-	800 mm	False	False	1297 mm	9005	2
PRO-4280TS.P1P2	19" Server Cabinet PRO 42U, 800x1000 mm, F=1-P R=2-P, RAL9005	black	1000 mm	Three-point	Steel	Steel	1360 kg	42 U	Three-point	800 mm	False	False	1963 mm	9005	2

This datasheet was created automatically on 02-01-2023 . Technical changes reserved.



DATASHEET

19" Server Cabinet PRO 42U, 800x1000 mm, F=1-P R=2-P, RAL9005

PRO-4780TS.P1P2	19" Server Cabinet PRO 47U, 800x1000 mm, F=1-P R=2-P, RAL9005	black	1000 mm	Three-point	Steel	Steel	1360 kg	47 U	Three-point	800 mm	False	False	2186 mm	9005	2
PRO-4280GR.P1P2	19" Server Cabinet PRO 42U, 800x1000 mm, F=1-P R=2-P, RAL7035	grey	1000 mm	Three-point	Steel	Steel	1360 kg	42 U	Three-point	800 mm	False	False	1963 mm	7035	2

This datasheet was created automatically on 02-01-2023 . Technical changes reserved.

