

## MONITORED PDU

### PDU technical data of series **MXLJ2WNY6x**

- 36 IEC320C13 sockets outlet max. 10A/230V.
- 6 IEC320C19 sockets outlet max. 16A/230V.
- Sockets are colour-coded by phase (black, red and grey).
- Plastic elements colour: black RAL9005.
- Natural anodized aluminium body.
- Dimensions without mounting brackets: width 44mm, length 1635mm, depth 46mm.
- Vertical mounting in 19" rack- 0U.
- Mounting brackets for installation in 4 orientations.
- Supply cable H05VVF.5G2,5mm<sup>2</sup> (halogen-free option available) in white or black colour terminated IEC309 16A plug red 3-phase. Length up to 10m.
- Maximum current 3x16A (11 040 W).
- Mains voltage 230/400 VAC.
- Three AC ammeters with 3 digits LED display.
  - Measurement range 0,1...16A.
  - Measurement accurate ±2,5%.
- Protection level IP20.
- Declaration of Conformity CE.
- Built-in web server monitoring function of the current load of individual circuit blocks with Watchdog over IP function.
- Web interface: Ethernet RJ45 (Ethernet 10/100BaseT).
- Protocols: TCP / IP, HTTP, SNMP, SMTP, Syslog, DHCP
- Standard warranty 2 years.



#### Power supply length cable

2m	3m	5m
<b>MXLJ2WNY62</b>	<b>MXLJ2WNY63</b>	<b>MXLJ2WNY65</b>