

3 PHASE PDU- MONITORED

PDU technical data of series MXLJ3AMJ6x

- 18 IEC320C13 sockets outlet max. 10A/230VAC.
- 6 IEC320C19 sockets outlet max. 16A/230VAC.
- Sockets are located in 6 blocks.
- Each block is protected by circuit breaker for overload and short circuit.
- Tripping characteristic - type C, 16A, 1-pole.
- Plastic elements colour: light-grey RAL7035.
- Natural anodized aluminium body.
- Dimension without mounting brackets: width 44mm, length 1742mm, depth 70mm.
- Vertical mounting in 19" rack- 0U.
- Mounting brackets for installation in 4 orientations.
- Supply cable H05VVF.5G4,0mm² in white colour terminated IEC309 32A plug red 3-phase. Standard length up to 10m.
- Maximum current 3x32A (22 080 W).
- Mains voltage 230 VAC
- Six AC ammeters with 3 digits LED display.
 - Measurement range 0,1...16A.
 - Measurement accurate ±2,5%.
- Built-in web server monitoring function of the current load of individual circuit blocks.
- Web interface: Ethernet RJ45 (Ethernet 10/100BaseT)
- Protocols: TCP / IP, HTTP, SNMP, SMTP, Syslog, DHCP
- Protection level IP20.
- Declaration of Conformity CE.
- Standard warranty 2 years.

Power supply length cable		
2m	3m	5m
MXLJ3AMJ62	MXLJ3AMJ63	MXLJ3AMJ65

