

DATASHEET

19" Wall Housing IP55, Glass Door, Depth 600 mm, RAL7035



Description

Steel sheet housing with welded corpus, completely pre-assembled
Right- and left-sided metal covered air inlets for passive ventilation
Side walls not detachable
Roof hinged, inner roof prepared for mounting of Plug&Play fan unit Art.-No. 691656GR (cable not included, please order separately, e.g. Art.-No. EK504.x)
Bottom with PG glands 1 x PG48, 2 x PG21 and 3 x Ø 20 mm PVC blind grommets
For depth 450 mm inside 2 x 19" profile rails front-sided, galvanised, with numbering of rack units (U)
For depth 600 mm inside 4 x 19" profile rails (2 front, 2 rear), galvanised, with numbering of rack units (U)
Front door with window of certified safety glass and 3-point bar locking, lockable, with profile half-cylinder acc. to DIN 18252 / EN1303
Profile half-cylinder exchangeable by customer
Cabinet parts inside completely earthed
Max. load 100 kg
Paint finish RAL7035, light grey
Protection degree IP55
Plinth for use as standing cabinet available as option
Included accessories: 4 x Wall mount angle, 2 x key

General data

Mounting level	Front side
Type of profile rail	L-shaped
Type of ventilation	Passive

This datasheet was created automatically on 26-05-2022. Technical changes reserved.



19" Wall Housing IP55, Glass Door, Depth 600 mm, RAL7035

General data

Modular spacing	482.6 mm (19 inch)
With roof plate	True
With earthing	True
With front door	True
With sidewall	True
Demountable	False
Model	With permanent frame
Material	Steel
Surface finishing	With powder coating
Degree of protection (IP)	IP55
Number of doors	1
Number of cartons	1

Available variants

Article no.	Title	Number of height units	Width	Height	Depth	Max. Load	RAL-number	Colour
691707IP55.2G	19" Wall Housing IP55, 7U, Glass Door, Depth 600 mm, RAL7035	7	600 mm	410 mm	600 mm	100 kg	7035	grau
691709IP55.2G	19" Wall Housing IP55, 9U, Glass Door, Depth 600 mm, RAL7035	9	600 mm	500 mm	600 mm	100 kg	7035	grau
691712IP55.2G	19" Wall Housing IP55, 12U, Glass Door, Depth 600 mm, RAL7035	12	600 mm	630 mm	600 mm	100 kg	7035	grau
691716IP55.2G	19" Wall Housing IP55, 16U, Glass Door, Depth 600 mm, RAL7035	16	600 mm	810 mm	600 mm	100 kg	7035	grau
691720IP55.2G	19" Wall Housing IP55, 20U, Glass Door, Depth 600 mm, RAL7035	20	600 mm	1000 mm	600 mm	100 kg	7035	grau

accessory

691750WIP.2	Plinth for 19" Wall Housing IP55, Depth 600 mm
691675.07	19" Profile Rails for Wall Housing IP55

spare part

102131.2	Hinge for Wall Housing IP55
----------	-----------------------------

This datasheet was created automatically on 26-05-2022 . Technical changes reserved.

DATASHEET

19" Wall Housing IP55, Glass Door, Depth 600 mm, RAL7035

spare part

691666	Spare Filter for Wall Housing IP55
102115.2	Spare Keys for Wall Housing IP55 and 3+5U

This datasheet was created automatically on 26-05-2022 . Technical changes reserved.

